

MP 590 - Spécifications techniques



Description

MP 590 est un pneu agro-industriel pour les opérations de chargement avec les chargeurs télescopiques et les chariots élévateurs. Ce pneu offre une traction et une stabilité excellentes en même temps qu'une durabilité augmentée.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Chargeuse télescopique

Industriel: Chariot élévateur • Chargeuse télescopique •

Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	18 - 22.5 (445/65 - 22.5)

Dimensions US Standard

Usa code	94014729
Ply Rating	16
Section Width (inch)	18.9
Overall Diameter (inch)	46.9
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	139.1
Rim Rec	14.0
ECE	E11-106R-003019

Load capacity (lbs)

mph / psi	80
25 DW	10750
20 DW	12010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..