



MULTI RIB - Fiche de données



Description

MULTI RIB est un pneu agro-industriel pour le travail de la terre et les applications de transport avec tracteurs 2WD/2RM et outils agricoles. Ce pneu offre une manœuvrabilité exceptionnelle pendant toute sa durée de vie. Il y a des différentes versions pour répondre à tous les exigences : une version « aramid belted » avec ceintures en aramide pour garantir une résistance exceptionnelle aux crevaisons et une version « HD » avec un mélange particulièrement résistant aux coupures et déchirures.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Tracteur 2WD • Outilage agricole

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
11.00 - 16	ARAMID BELTED HD	94052516	12	W10 L	W 8 ; W 8 L	12.4	36.6	TL	E11-106R-005377
11.00 - 16	HD	94061624	12	W10 L	W 8 ; W 8 L	12.4	36.6	TL	
11.00 - 16	STANDARD	94006199	12	W10 L	W 8 ; W 8 L	12.4	36.6	TL	E11-106R-004649

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..