

MULTIMAX MP 513 - Spécifications techniques



Description

MULTIMAX MP 513 a été conçu par BKT pour les véhicules polyvalents dans le cadre des services municipaux de voirie et de transport pour les applications agricoles et industrielles. Grâce à sa carcasse robuste en nylon renforcée avec des ceintures d'acier, MULTIMAX MP 513 permet de transporter des charges lourdes à de grandes vitesses en assurant une expérience de conduite confortable. Il garantit une vie opérationnelle plus longue, une traction excellente ainsi que des propriétés d'autonettoyage exceptionnelles. Il est idéal pour les véhicules universels et les camions d'engrais.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule universel • Camion d'engrais
Industriel: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	365/70 R 18 MPT
LI/SS	133 G

Dimensions US Standard

Usa code	94051366
Section Width (inch)	14.2
Overall Diameter (inch)	38.1
Static Loaded Radius (inch)	17.6
Rolling Circumference (inch)	116.3
Rim Rec	11
Rim Alt	11 SDC ; 12 ; 12 SDC
ECE	E11-54R-0016138

Load capacity (lbs)

mph / psi	23	29	36	44	51	54
55	2380	2820	3350	3880	4410	4540
40	2580	3040	3640	4210	4780	4940
25	2760	3240	3860	4450	5070	5220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..