

MULTIMAX MP 513 - Spécifications techniques



Description

MULTIMAX MP 513 a été conçu par BKT pour les véhicules polyvalents dans le cadre des services municipaux de voirie et de transport pour les applications agricoles et industrielles. Grâce à sa carcasse robuste en nylon renforcée avec des ceintures d'acier, MULTIMAX MP 513 permet de transporter des charges lourdes à de grandes vitesses en assurant une expérience de conduite confortable. Il garantit une vie opérationnelle plus longue, une traction excellente ainsi que des propriétés d'autonettoyage exceptionnelles. Il est idéal pour les véhicules universels et les camions d'engrais.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule universel • Camion d'engrais
Industriel: Véhicule universel

Version	STANDARD
Type	TL
Tyre Size	425/75 R 20 MPT
LI/SS	148 G

Dimensions US Standard

Usa code	94034703
Section Width (inch)	16.6
Overall Diameter (inch)	45.1
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	137
Rim Rec	13
Rim Alt	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12
ECE	E11-54R-0016141

Load capacity (lbs)

mph / psi	23	29	36	44	51	58
55	3390	3990	4740	5490	6220	6940
40	3690	4330	5150	5960	6750	7540
25	3910	4600	5460	6320	7150	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 23:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..