



MULTIMAX MP 515 - Fiche de données



Description

MULTIMAX MP 515 est un pneu radial agro-industriel pour les véhicules universels et les camions d'engrais. Il est adapté pour les applications municipalité et de transport. Ce pneu présente un dessin unique de la bande de roulement, ce qui se traduit par un grand confort de conduite sur route et par d'excellentes qualités d'autonettoyage, ainsi qu'une excellente traction. La carcasse robuste en nylon avec des ceintures d'acier et les épaules arrondies assurent une durabilité exceptionnelle. MULTIMAX MP 515 est le pneu idéal même à grande vitesse (90km/h).

UM

US Standard

Construction

RADIAL

Machinery

Agriculture: Véhicule universel • Camion d'engrais

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
405/70 R 20 MPT	STANDARD	94056545	136 G	13	13 SDC ; 12 SDC ; 11 SDC ; 11	16	42.4	19.4	129.4	TL	E4-54R-0016565
425/75 R 20 MPT	STANDARD	94055975	148 G	13	13 SDC ; 11 SDC ; 12 SDC ; 11 ; 12	16.6	45.1	20.6	137.4	TL	E11-54R-0017872
445/65 R 22.5 MPT	STANDARD	94057207	160 G	13	14	17.5	45.3	20.7	139.1	TL	E11-54R-0017868

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 01:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..