

MULTIMAX MP 529 - Spécifications techniques



Description

MULTIMAX MP 529 est un pneu radial polyvalent avec ceintures d'acier pour chargeurs télescopiques dans les applications industrielles. Sa bande de roulement a été spécialement conçue pour les surfaces dures. Le flanc robuste du pneu et une plus grande surface d'empreinte assurent une stabilité exceptionnelle en mode levage. MULTIMAX MP 529 est également pourvu d'une carcasse robuste résistante aux crevaisons et est fabriqué à partir d'un composant particulièrement résistant aux coupures et déchirures, pour une excellente durabilité et une longue vie du pneu.

UM

International Standard

Construction



RADIAL

Machinery

Industriel: Chargeuse télescopique

Version	STEEL BELTED
Type	TL
Tyre Size	340/80 R 18
LI/SS	143 A8/B

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	1001
Static Loaded Radius (mm)	445
Rolling Circumference (mm)	3007
SRI (mm)	475
Rim Rec	11 ; 11 SDC ; W 11
Rim Alt	W 10 ; 12 ; 12 SDC
ECE	E11-106R-002972

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1310	1555	1775	2020	2265	2430	2725	-	-
40	1310	1555	1775	2020	2265	2430	2725	-	-
30	1405	1665	1900	2165	2425	2600	2920	-	-
25	1455	1725	1970	2240	2515	2695	3025	-	-
10 Cyc.	1600	1965	2315	2660	3030	3295	3725	3930	4090
Static	2450	3010	3545	4080	4640	5050	5710	6020	6270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..