

MULTIMAX MT 518 - Spécifications techniques



Description

MULTIMAX MT 518 a été spécialement conçu pour les camions militaires. C'est un pneu avec dessin de la bande de roulement à blocs et ceintures d'acier qui se distingue de par une résistance élevée aux perforations ainsi que par une extraordinaire stabilité. De plus, MULTIMAX MT 518 supporte des vitesses élevées et bénéficie d'un cycle de vie plus long.

UM

US Standard

Construction

 RADIAL

Machinery

Industriel: Camion militaire

Version	STANDARD
Type	TL
Tyre Size	36 X 12.5 R 16.5
LI/SS	129 N

Dimensions US Standard

Usa code	94039517
Section Width (inch)	12.4
Overall Diameter (inch)	35.5
Static Loaded Radius (inch)	16.5
Rolling Circumference (inch)	108.6
Rim Rec	9.75
ECE	E11-54R-0017917

Load capacity (lbs)

mph / psi	65
85	4080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 12:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..