

PAC MASTER PLUS - Spécifications techniques



Description

PAC MASTER PLUS est un pneu diagonal pour compacteurs caractérisé par une zone de contact plus large qui offre une plus grande stabilité. Il est réalisé dans un mélange spécial qui lui confère une grande résistance à la chaleur. PAC MASTER PLUS assure un cycle de vie plus long du pneu.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Compacteur

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	10
Section Width (mm)	270
Overall Diameter (mm)	1005
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005276

Load capacity (Kg)

km/h / bar	5.25
10	3650
15	2900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..