

## PORT KING PLUS - Fiche de données



### Description

PORT KING PLUS a été quant à lui spécialement conçu pour les reach stackers dans les applications de logistique/transport intermodal. La bande de roulement profonde avec les crampons robustes est réalisée dans un mélange spécial qui allonge la durée de vie du pneu. Il existe aussi une version avec un mélange particulièrement résistant aux fissures dans les rainures de la bande de roulement "GCRC" (groove crack resistant compound).

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriel: Reach stacker

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
18.00 - 25	GCRC	IND4	40	13.00 /2.5	15.00/2.5	528	1675	765	4955	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..