

PORTMAX PT 93 - Spécifications techniques



Description

PORTMAX PT 93 est un pneu pour tracteurs de manœuvre et remorques spécialement conçu pour des opérations de service lourd dans les terminaux portuaires et les pôles logistiques. Le mélange spécial antistatique de la bande de roulement garantit une résistance exceptionnelle à l'usure et à la chaleur, y compris dans des conditions extrêmes. PORTMAX PT 93 est idéal pour toutes les opérations qui nécessitent une manutention élevée, en outre, il assure une excellente adhérence et une durabilité avancée.

UM

US Standard

Construction

 RADIAL

Machinery

Industriel: Tracteur de manœuvre • Remorque

Version	INDUSTRIAL
Type	TL
Tyre Size	315/60 R 22.5
LI/SS	170 A8

Dimensions US Standard

Usa code	94067855
Overall Width (inch)	12.1
Overall Diameter (inch)	38
Rim Rec	9.75
Rim Alt	9.00

Load capacity (lbs)

mph / psi	145
25	13200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..