

POWER TRAX HD - Fiche de données



Description

Le pneu POWER TRAX HD premium est spécialement conçu pour les équipements dans les ports et les mines souterraines. Sa bande de roulement profonde, son côté extra-épais et sa carcasse résistante lui confèrent une durabilité exceptionnelle, minimisant les risques de crevaison et de dommages accidentels. Le pneu présente une excellente résistance aux coupures et aux éclats, ce qui le rend particulièrement adapté aux surfaces rugueuses et dures. Le protège-jante de conception spécifique assure une protection contre les crevaisons et les impacts et chocs au niveau du rebord de la jante.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneur

OTR: Véhicule miniers souterrains

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	Tread Depth	ECE
12.00 - 20	IMPLEMENT	172 A8	20	8.50	9.0	320	1150	TT	34	E11-106R-003422
12.00 - 20	IMPLEMENT	173 A8	28	8.50	9.0	320	1150	TT	34	E11-106R-003348
12.00 - 20	STANDARD		20	8.50	9.0	320	1150	TT	34	
12.00 - 20	STANDARD		28	8.50	9.0	320	1150	TT	34	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 23:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..