

POWER TRAX - Fiche de données



Description

Le POWER TRAX est un pneu haut de gamme spécialement conçu pour le service à usage intensif sur remorque portuaire, chariot de conteneurs vides ou machines d'extraction minière ECH et souterraine. Sa bande de roulement profonde et sa carcasse robuste offrent une durabilité exceptionnelle, réduisant au minimum le risque de crevaison et de dommage accidentel. Le POWER TRAX est le pneu idéal pour les opérations lourdes et difficiles, grâce au composé de sa bande de roulement unique qui offre une excellente résistance aux coupures et aux déchirures.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide
OTR: Véhicule miniers souterrains

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	Tread Depth
355/65 - 15	STANDARD	170 A5	24	9.75		335	830	380	2530	TL	28
12.00 - 20	STANDARD	176 A5	20	8.5	9.0	320	1150			TT	34

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..