

POWERTRAILER SR 331 - Spécifications techniques



Description

Le POWERTRAILER SR 331 est le tout nouveau pneu radial All Steel (Tout Acier) de BKT, spécialement conçu pour les remorques et les camions-citernes dans les applications de transport. Développé pour une utilisation sur le terrain et sur la route, le POWERTRAILER SR 331 se distingue par ses bonnes propriétés de flottaison dans les champs ainsi que par son excellente traction sur l'asphalte ou d'autres surfaces dures et améliorées. La construction All Steel est synonyme de capacité de charge élevée, de stabilité extraordinaire de la carcasse et d'une durabilité prolongée du pneu. La nervure spéciale du flanc offre une protection exceptionnelle contre les chocs et les effets du frottement du pneu, tandis que le talon hexagonal renforcé avec bandelette garantit que le pneu s'adapte parfaitement à la jante. En outre, la bande de roulement multiblocs garantit une résistance au roulement réduite, une pression de contact uniforme et une bonne tenue de route. Grâce à toutes ces caractéristiques, POWERTRAILER SR 331 est synonyme d'économie de carburant et de confort routier.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	IMPLEMENT
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	165 D

Dimensions International Standard

Overall Width (mm)	555
Overall Diameter (mm)	1245
Static Loaded Radius (mm)	565
Rolling Circumference (mm)	3775
SRI (mm)	600
Rim Rec	AG 16.00
Rim Alt	17.00 ; AG18.00
ECE	E11-106R-0010087

Load capacity (Kg)

km/h / bar	3.2	3.6	4	4.5	5
10	6860	7505	8255	8810	9270
25	6020	6590	7245	7735	8135
40	5180	5670	6235	6655	7005
50	4610	5045	5550	5925	6230
65	3810	4170	4585	4895	5150
70	3465	3795	4170	4455	4685

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..