



## RIB 324 - Fiche de données



### Description

RIB 324 a été particulièrement conçu avec dessin à blocs de la bande de roulement et une large zone de contact pour fournir une grande stabilité ainsi qu'Excellent qualités de flottaison sur sol meuble ou des terrains sableux. La carcasse en nylon et le flanc robustes associés au mélange spécial de la bande de roulement garantissent une excellente résistance aux coupures et à l'usure ainsi qu'une capacité de charge plus élevée.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Outilage agricole

Industriel: Remorque

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
66 X 44.00 - 25	STANDARD	20	36.0 TH		1110	1700	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..