

RIB 774 (B) - Fiche de données



Description

RIB 774 (B) est un pneu à taille basse pour outils agricoles, idéal pour l'agriculture moderne. Ce pneu convient aussi bien pour les applications sur route que hors route avec les outils agricoles et les remorques. Ce pneu offre une grande capacité de charge ainsi qu'un long cycle de vie. Une version « HD » est disponible pour les opérations pénibles.

UM

International Standard

Construction

✚ BIAS

Machinery

Agriculture: Outillage agricole • Remorque
Industriel: Remorque

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
15.0/55 - 17	STANDARD	141 A8	14	13.00	13	391	850	377	2490	TL	E11-106R-004311
15.0/55 - 17	STANDARD	134 A8	10	13.00	13	391	850	377	2490	TL	E11-106R-004309

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 08:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..