

## RIDEMAX FL 693 M - Spécifications techniques



### Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Véhicule citerne • Remorque

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 500/45 R 22.5 |
| LI/SS     | 146 D/143 E   |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 503            |
| Overall Diameter (mm)      | 1022           |
| Static Loaded Radius (mm)  | 455            |
| Rolling Circumference (mm) | 3114           |
| SRI (mm)                   | 500            |
| Rim Rec                    | AG 16.00       |
| ECE                        | E4-106R-000786 |

## Load capacity (Kg)

| km/h / bar | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|
| 70         | 1000 | 1120 | 1390 | 1585 | 1830 | 2075 | 2265 | 2480 | 2725 |
| 65         | 1095 | 1230 | 1530 | 1740 | 2010 | 2280 | 2490 | 2730 | 3000 |
| 50         | 1330 | 1490 | 1855 | 2110 | 2435 | 2760 | 3015 | 3305 | 3630 |
| 40         | 1495 | 1675 | 2085 | 2370 | 2735 | 3105 | 3390 | 3715 | 4080 |
| 25         | 1735 | 1945 | 2420 | 2750 | 3180 | 3605 | 3935 | 4315 | 4740 |
| 10         | 1975 | 2215 | 2755 | 3135 | 3620 | 4105 | 4485 | 4915 | 5400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 10:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..