

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	650/65 R 30.5
LI/SS	176 D

Dimensions US Standard

Usa code	94075324
Section Width (inch)	25.4
Overall Diameter (inch)	63.9
Static Loaded Radius (inch)	28.9
Rolling Circumference (inch)	194.4
Rim Rec	AG 20.00
ECE	E11-106R-009076

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	4560	5280	6000	7270	8410	9700	10980	11840	13120	14250
40	5020	5800	6580	7990	9240	10650	12060	13000	14410	15650
30	6070	7020	7960	9670	11190	12890	14590	15730	17440	18950
25	6820	7890	8950	10870	12570	14480	16400	17680	19600	21300
15	7930	9160	10390	12620	14590	16820	19050	20530	22760	24730
5	9020	10430	11840	14370	16630	19170	21700	23390	25920	28170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 10:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..