

RM 2002 - Spécifications techniques



Description

RM 2002 est un pneu adapté pour les opérations de transport avec remorques et camions légers tant sur route que hors route. Ce pneu assure une longue durabilité et des performances élevées pendant tout le cycle de vie du produit. Sa version "industrielle" est idéale pour les grues mobiles "pick & carry".

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Industriel: Grue automotrice

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions US Standard

Usa code	94022656
Ply Rating	16
Section Width (inch)	11.9
Overall Diameter (inch)	43.3
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

Load capacity (lbs)

mph / psi	115	105
62 LS	7165	-
62 LD	-	6395

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..