

## RM 500 - Spécifications techniques



### Description

RM 500 est un pneu radial avec ceintures d'acier, adapté pour les applications de récolte avec outillage agricole. Le pneu est équipé d'une carcasse robuste et un dessin particulier de la bande de roulement qui offrent une capacité de charge élevée en même temps qu'une excellente résistance aux coupures et lacérations. Grâce à son empreinte large, RM 500 assure une excellente répartition de la pression sur le terrain avec un compactage réduit du sol, en plus d'une traction exceptionnelle.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Moissonneuse

|                    |                 |
|--------------------|-----------------|
| Version            | STEEL BELTED    |
| Type               | TL              |
| Tyre Size          | 500/80 R 28     |
| LI/SS              | 176 A8 / 164 A8 |
| LI/SS DRIVE WHEEL  | 164 A8          |
| LI/SS FREE ROLLING | 176 A8          |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94063697        |
| Section Width (inch)         | 19.8            |
| Overall Diameter (inch)      | 58.9            |
| Static Loaded Radius (inch)  | 25              |
| Rolling Circumference (inch) | 171.5           |
| Rim Rec                      | W 16 L          |
| Rim Alt                      | W 15 L          |
| ECE                          | E11-106R-005990 |

## Load capacity (lbs)

| mph / psi       | 12   | 15   | 17   | 23   | 29    | 35    | 41    | 46    |
|-----------------|------|------|------|------|-------|-------|-------|-------|
| 25 Free Rolling | 6110 | 7040 | 7830 | 9710 | 11120 | 12840 | 14560 | 15650 |
| 25 Drive Wheel  | 4300 | 4960 | 5510 | 6830 | 7830  | 9040  | 10250 | 11020 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..