

RM 500 - Spécifications techniques



Description

RM 500 est un pneu radial avec ceintures d'acier, adapté pour les applications de récolte avec outillage agricole. Le pneu est équipé d'une carcasse robuste et un dessin particulier de la bande de roulement qui offrent une capacité de charge élevée en même temps qu'une excellente résistance aux coupures et lacérations. Grâce à son empreinte large, RM 500 assure une excellente répartition de la pression sur le terrain avec un compactage réduit du sol, en plus d'une traction exceptionnelle.

UM

International Standard

Construction

RADIAL

Machinery

Agriculture: Moissonneuse

Version	STEEL BELTED
Type	TL
Tyre Size	600/65 R 28
LI/SS	168 A8 / 156 A8
LI/SS DRIVE WHEEL	156 A8
LI/SS FREE ROLLING	168 A8

Dimensions International Standard

Section Width (mm)	590
Overall Diameter (mm)	1486
Static Loaded Radius (mm)	640
Rolling Circumference (mm)	4340
SRI (mm)	700
Rim Rec	W 18 L
Rim Alt	W 20 L
ECE	E11-106R-005993

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0
40 Free Rolling	3080	3530	3980	4820	5600
40 Drive Wheel	2200	2520	2840	3440	4000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..