

ROCK GRIP IND4 (RS) - Spécifications techniques



Description

Le ROCK GRIP PORT INDUSTRIAL IND-4 (RS) est un pneu à carcasse radiale conçu pour les gerbeurs dans plusieurs applications, notamment la manutention industrielle et les aciéries. Le composé spécial ROCK GRIP garantit une résistance particulière à la chaleur ainsi qu'une stabilité et une durabilité optimales.

UM

US Standard

Construction

✚ BIAS

Machinery

Industriel: Reach stacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

Dimensions US Standard

Usa code	94030224
Ply Rating	36
Overall Width (inch)	20.1
Overall Diameter (inch)	74.3
Static Loaded Radius (inch)	34.2
Rolling Circumference (inch)	219.9
Rim Rec	13.00/2.5
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	55100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..