

ROCK GRIP IND4 (ECH) - Spécifications techniques



Description

Le ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) est un pneu à carcasse diagonale conçu pour chariots de conteneurs vides dans plusieurs applications, notamment la manutention industrielle et les aciéries. Le composé spécial ROCK GRIP garantit une résistance particulière à la chaleur ainsi qu'une stabilité et une durabilité optimales

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	647
Rolling Circumference (mm)	4173
Rim Rec	10.00 W
TRA Code	IND4

Load capacity (Kg)

km/h / bar	10.00
10	14175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..