

ROCK GRIP IND4 (ECH) - Fiche de données



Description

Le ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) est un pneu à carcasse diagonale conçu pour chariots de conteneurs vides dans plusieurs applications, notamment la manutention industrielle et les aciéries. Le composé spécial ROCK GRIP garantit une résistance particulière à la chaleur ainsi qu'une stabilité et une durabilité optimales

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Chariot porte-conteneurs vide

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 - 24	PORT INDUSTRIAL	94046287	IND4	20	8.5	8.0	12.4	49.8	23.4	147.8	TT
12.00 - 24	PORT INDUSTRIAL	94047413	IND4	24	8.5	8.0	12.4	49.8	23.4	147.8	TT
14.00 - 24	PORT INDUSTRIAL	94049752	IND4	28	10.00 WA	10.00 VA	14.8	55.5	25.5	164.3	TL
14.00 - 24	PORT INDUSTRIAL	94059201	IND4	32	10.00 WA	10.00 VA	14.8	55.5	25.5	164.3	TL
14.00 - 24	PORT INDUSTRIAL	94031139	IND4	24	10.00 W		14.8	55.5	25.5	164.3	TL
14.00 - 24	PORT INDUSTRIAL	94030743	IND4	28	10.00 W		14.8	55.5	25.5	164.3	TL
14.00 - 24	PORT INDUSTRIAL	94030590	IND4	32	10.00 W		14.8	55.5	25.5	164.3	TL
16.00 - 25	PORT INDUSTRIAL	94052059	IND4	32	11.25/2.0	13.00/2.0	18.5	60	27.5	177.7	TL
16.00 - 25	PORT INDUSTRIAL	94060412	IND4	36	11.25/2.0	13.00/2.0	18.5	60	27.5	177.7	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..