

ROCK STAR L4 - Fiche de données



Description

ROCK STAR LOADER a été particulièrement conçu pour les grues et les chargeurs. En plus d'une excellente traction, le mélange unique de la bande de roulement est particulièrement résistant aux coupures et déchirures. ROCK STAR LOADER est un pneu à 24 plis pour une capacité de charge élevée alors que longévité.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeur

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	Type	TKPH
14.00 - 24	STANDARD	L4	24	10.00 WA	10.00 VA	390	1425	TT	1

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 08:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..