

SAND STAR - Fiche de données



Description

SAND STAR est un pneu avec dessin de la bande de roulement à blocs, particulièrement conçu pour les remorques. Il assure une excellente traction sur les surfaces sableuses et un contact optimal avec le terrain, ce qui permet de réduire le compactage du sol.

UM

International Standard

Construction

✚ BIAS

Machinery

Industriel: Remorque

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
9.00 - 13	STANDARD	116 A8	8	5.50 F	5.50 WB	245	784	TT	E11-106R-005261
9.00 - 13	STANDARD	116 A8	8	5.50 F	5.50 WB	245	784	TL	E11-106R-005261
9.00 - 13	STANDARD	108 D	6	5.50 F	5.50 WB	245	784	TL	E11-106R-005296
9.00 - 13	STANDARD	119 A8	10	5.50 F	5.50 WB	245	784	TT	E11-106R-005263
9.00 - 13	STANDARD	119 A8	10	5.50 F	5.50 WB	245	784	TL	E11-106R-005263
9.00 - 13	STANDARD	108 D	6	5.50 F	5.50 WB	245	784	TT	E11-106R-005296

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..