

SIERRA MAX PRO - Fiche de données



Description

Le pneu SIERRA MAX PRO de BKT est idéal pour les véhicules tout-terrain dans les applications ATV, y compris les courses côte à côte. Sa construction radiale et sa surface d'empreinte spéciale plus large permettent une conduite plus souple, ainsi qu'une traction latérale et avant optimisée. Des crampons spéciaux et solides ont été spécialement étudiés pour offrir une excellente traction et adhérence sur le terrain. Ces caractéristiques assurent une conduite remarquablement confortable, garantissant ainsi la sécurité et le contrôle de la conduite. Le SIERRA MAX PRO offre d'excellentes performances sur tous les types de terrain, des terrains durs aux sols meubles.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule ATV

SIZE	Version	Star R	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
AT 25 X 8 R 12	STANDARD	***	43 N	6.5		200	630	287	1860	TL	E11-75R-005088
AT 27 X 11 R 14	STANDARD	***	56 N	9.00		285	708	336	2145		E11-75R-005098

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..