

SIERRA MAX - Spécifications techniques



Description

SIERRA MAX est le pneu BKT tant pour les applications ATV/VTT que pour les prés et jardins. Grâce à sa construction radiale, ce pneu offre une conduite beaucoup plus souple et confortable même sur des terrains extrêmement difficiles comme le désert ou les surfaces terreuses et rocheuses. Le dessin particulier de la bande de roulement et son empreinte plus large lui confèrent une traction antérieure et latérale incomparable.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule ATV

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 9 R 14
LI/SS	50 N

Dimensions US Standard

Usa code	94052615
Section Width (inch)	9.1
Overall Diameter (inch)	27.6
Static Loaded Radius (inch)	12.4
Rolling Circumference (inch)	81.5
Rim Rec	7.00
Star Rating	***
ECE	E11-75R-005099

Load capacity (lbs)

mph / psi	7
87	420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..