

SKID POWER HD (A) - Spécifications techniques



Description

SKID POWER HD (A) a été conçu pour les chargeuses compactes dans les applications de bâtiment. Ce pneu se distingue de par la bande de roulement extra profonde et la protection des flancs, qui lui confèrent une excellente résistance aux coupures et déchirures ainsi qu'une extraordinaire durabilité. SKID POWER HD (A) est le pneu idéal pour les surfaces terreuses et les conditions pénibles.

UM

US Standard

Construction

✚ BIAS

Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	33 X 15.5 - 16.5
LI/SS	151 A2

Dimensions US Standard

Usa code	94060825
Ply Rating	14
Section Width (inch)	15.5
Overall Diameter (inch)	33
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	100.9
Rim Rec	13.00
ECE	E11-106R-006606

Load capacity (lbs)

mph / psi	70
5	7600
10	6005
15	5555

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..