

# SKID POWER - Spécifications techniques



## Description

SKID POWER a été conçu pour les chargeuses compactes dans les applications de bâtiment; il fait preuve d'une excellente traction et a des capacités élevées d'auto-nettoyage. Ce pneu se distingue de par la bande de roulement extra profonde et la protection particulière des flancs, ce qui assure une excellente résistance aux coupures et déchirures ainsi qu'une durabilité extraordinaire. SKID POWER est le pneu idéal pour les surfaces terreuses.

## UM

US Standard

## Construction

❖ BIAS

## Machinery

Industriel: Chargeur compact

Version	IMPLEMENT
Type	TL
Tyre Size	23 X 10.5 - 12
LI/SS DRIVE WHEEL	90 A8
LI/SS FREE ROLLING	90 A8

## Dimensions US Standard

Usa code	94076093
Ply Rating	6
Section Width (inch)	10.4
Overall Diameter (inch)	23.2
Rim Rec	8.5 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-008809

## Load capacity (lbs)

mph / psi	41
25 FR	1320
25 DW	1320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..