

SKID POWER - Spécifications techniques



Description

SKID POWER a été conçu pour les chargeuses compactes dans les applications de bâtiment; il fait preuve d'une excellente traction et a des capacités élevées d'auto-nettoyage. Ce pneu se distingue de par la bande de roulement extra profonde et la protection particulière des flancs, ce qui assure une excellente résistance aux coupures et déchirures ainsi qu'une durabilité extraordinaire. SKID POWER est le pneu idéal pour les surfaces terreuses.

UM

International Standard

Construction

❖ BIAS

Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	25 X 8.5 - 14
LI/SS	106 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	213
Overall Diameter (mm)	652
Static Loaded Radius (mm)	305
Rolling Circumference (mm)	1912
Rim Rec	7 JA
ECE	E11-106R-006265

Load capacity (Kg)

km/h / bar	3.40
10	965
15	765
25	705

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..