

SM 54 IND-4S - Spécifications techniques



Description

Le SM 54 IND-4S a été spécialement conçu pour la manutention de conteneurs vides et les reach stackers dans les applications de transport intermodal et de logistique. Il se caractérise par une grande stabilité en mode de levage et une bande de roulement profonde et lisse, qui offre une excellente résistance aux coupures permettant ainsi de garantir une plus longue durée de vie aux pneus.

UM

US Standard

Construction

 BIAS

Machinery

Industriel: Reach stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94015610
Ply Rating	28
Overall Width (inch)	16.9
Overall Diameter (inch)	57.9
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	171.4
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	L4S

Load capacity (lbs)

mph / psi	131
5	34200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..