

SM 68 (GK) - Spécifications techniques

Description

SM 68 a été spécialement conçu pour les karts. Le dessin lisse de la bande de roulement assure d'excellentes performances dans les activités sportives. Dureté Shore A 68.

UM

US Standard

Construction

✚ BIAS

Machinery

Agriculture: Kart



Version	STANDARD
Type	TL
Tyre Size	11 X 7.10 - 5

Dimensions US Standard

Usa code	94008032
Section Width (inch)	7.5
Overall Diameter (inch)	11.6
Rim Rec	6.75

Load capacity (lbs)

mph / psi	58
-	298

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..