

SNOW - RIDE (A) - Spécifications techniques



Description

SNOW-RIDE est particulièrement adapté pour les applications de municipalité/maintenance en conditions hivernales avec chargeuses et chargeurs compacts. Ce pneu se distingue de par une excellente traction et il est idéal pour les opérations sur la neige et la glace. Le dessin spécial de la bande de roulement élimine tout risque de dérapage en assurant un cycle de vie plus longue du pneu.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Chargeuse compacte

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions US Standard

Usa code	94044016
Ply Rating	10
Section Width (inch)	12
Overall Diameter (inch)	32.9
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	98.6
Rim Rec	9.75
Rim Alt	-

Load capacity (lbs)

mph / psi	65
5	5600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 15:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..