

## SR 713 - Spécifications techniques



### Description

SR 713 est un pneu radial **All Steel** (Tout Acier) doté de la technologie VF pour engins agricoles. Ce pneu est caractérisé par une carcasse robuste avec ceintures en acier multicouches et par une bande de roulement au dessin à rainures multiples qui garantissent une faible résistance au roulement ainsi qu'une usure uniforme de la bande de roulement. Grâce à son empreinte large, ce pneu VF assure un compactage réduit du sol. SR 713 se distingue tant en termes de performances que par sa fiabilité, tout en offrant d'excellents niveaux de vitesse même sur la route.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Outilage agricole

Version	STANDARD
Type	TL
Tyre Size	VF 445/65 R 22.5
LI/SS	176 D

## Dimensions US Standard

Usa code	94068944
Overall Width (inch)	17.3
Overall Diameter (inch)	45.7
Static Loaded Radius (inch)	21
Rolling Circumference (inch)	138.4
Rim Rec	13.00
Rim Alt	14.00
ECE	E11-106R-006976
TRA Code	I1

## Load capacity (lbs)

mph/psi	35	38	41	44	46	49	52	55	58	61	64	67	70	73	75	78
40	7850	8250	8800	9350	9650	10200	10500	11000	11700	12000	12800	13200	13600	13900	14800	15700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..