

SUPER TRAX HD - Spécifications techniques



Description

SUPER TRAX HD a été particulièrement conçu pour les chariots élévateurs dans les opérations de manutention de matériaux en service intensif, y compris les applications portuaires et les mines. La bande de roulement extra-profond, réalisée avec un mélange unique, assure un cycle de vie plus long du pneu. SUPER TRAX HD se distingue de par la carcasse robuste et le flanc renforcé avec le résultat d'une excellente stabilité et manœuvrabilité en mode de levage. Le bord de protection particulier de la jante protège le pneu dans la zone du rebord de la jante contre tout dommage à la rue ou dégonflage.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chariot élévateur

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

Dimensions International Standard

Ply Rating	12
Section Width (mm)	168
Overall Diameter (mm)	548
Static Loaded Radius (mm)	256
Rolling Circumference (mm)	1672
Rim Rec	4.00 E

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	1885
25 STEER WHEEL	1450
10 OTHER VEHICLES	1885
25 OTHER VEHICLES	1450
STATIC SIDE LOADER	2190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..