

SURE TRAX HD - Spécifications techniques



Description

SURE TRAX HD est un pneu avec dessin de la bande de roulement à blocs pour chargeuses compactes pour les applications dans le secteur bâtiment. Ce pneu fait preuve d'une excellente résistance aux coupures et déchirures, et d'une protection supérieure de la jante. SURE TRAX HD est idéal pour les surfaces asphaltées et les opérations de service pénible.

UM

US Standard

Construction

✚ BIAS

Machinery

Industriel: Chargeur compact

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions US Standard

Usa code	94017997
Ply Rating	12
Section Width (inch)	12.8
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	99.3
Rim Rec	9.75

Load capacity (lbs)

mph / psi	80
5	6320
10	4990
15	4610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..