

SURE TRAX HD - Spécifications techniques



Description

SURE TRAX HD est un pneu avec dessin de la bande de roulement à blocs pour chargeuses compactes pour les applications dans le secteur bâtiment. Ce pneu fait preuve d'une excellente résistance aux coupures et déchirures, et d'une protection supérieure de la jante. SURE TRAX HD est idéal pour les surfaces asphaltées et les opérations de service pénible.

UM

International Standard

Construction

BIAS

Machinery

Industriel: Chargeur compact

Version	INDUSTRIAL
Type	TL
Tyre Size	33 X 15.5 - 16.5
LI/SS	151 A2

Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	855
Rim Rec	13.00
ECE	E11-106R-006012

Load capacity (Kg)

	km/h / bar	4.80
	10	3450
	15	2725
	25	2520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 12:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..