

## TF 8181 - Spécifications techniques



### Description

TF 8181 est un pneu pour une utilisation aux champs et sur route conçu pour les tracteurs 2WD/2RM dans les applications de travail de la terre et de transport. Ce pneu assure un excellent niveau de braquage.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur 2WD

Industriel: Remorque

Version	STANDARD
Type	TT
Tyre Size	6.00 - 18
LI/SS	101 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	172
Overall Diameter (mm)	800
Static Loaded Radius (mm)	374
Rolling Circumference (mm)	2410
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-005253
TRA Code	F2

## Load capacity (Kg)

km/h / bar	4.20
30	825

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..