

TF 9090 - Spécifications techniques



Description

TF 9090 est un pneu conçu pour les micro tracteurs dans les opérations de travail de la terre. Le dessin spécial de la bande de roulement offre un excellent braquage sur le sol meuble.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Micro tracteur

Industriel: Remorque

Version	SPECIAL
Type	TT
Tyre Size	9.00 - 16
LI/SS	108 A8

Dimensions US Standard

Usa code	94038824
Ply Rating	10
Section Width (inch)	10.1
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	15.7
Rolling Circumference (inch)	100.3
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E11-106R-004114
TRA Code	F2

Load capacity (lbs)

mph / psi	60
25	2400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 13:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..