

TF 9393 - Spécifications techniques



Description

TF 9393 est un pneu avant pour l'agriculture particulièrement conçu pour les micro tracteurs dans les applications de travail de la terre. Il est particulièrement adapté sur un sol meuble. La bande de roulement est caractérisée par une large partie centrale et par des côtes dans la zone de l'épaule. Le dessin particulier de la bande de roulement assure un excellent braquage sur toutes les surfaces.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Micro tracteur

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16
LI/SS	103 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	210
Overall Diameter (mm)	810
Rim Rec	5.50 F
Rim Alt	5.00 F ; 6.00 F
TRA Code	F2

Load capacity (Kg)

km/h / bar	3.70
30	875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 00:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..