

## TR 138 - Spécifications techniques



### Description

TR 138 a été spécialement conçu pour les chargeuses télescopiques et les chargeuses pelleteuses dans l'agriculture et il est particulièrement adapté au travail de la terre et pour les applications de pulvérisation. Excellente traction, capacité d'auto-nettoyage et stabilité sont les atouts qui font de TR 138 le pneu idéal même dans les conditions de terrain les plus critiques.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agriculture: Chargeuse-pelleteuse • Chargeuse télescopique

Version	STANDARD
Type	TL
Tyre Size	17.5L - 24
LI/SS	151 A8

## Dimensions US Standard

Usa code	94061877
Ply Rating	12
Section Width (inch)	17.7
Overall Diameter (inch)	50.8
Static Loaded Radius (inch)	22.7
Rolling Circumference (inch)	151
Rim Rec	DW 15L
Rim Alt	DW 14L
ECE	E11-106R-005232

## Load capacity (lbs)

mph / psi	25
39	7605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..