

TR 138 - Fiche de données



Description

TR 138 a été spécialement conçu pour les chargeuses télescopiques et les chargeuses pelleteuses dans l'agriculture et il est particulièrement adapté au travail de la terre et pour les applications de pulvérisation. Excellente traction, capacité d'auto-nettoyage et stabilité sont les atouts qui font de TR 138 le pneu idéal même dans les conditions de terrain les plus critiques.

UM

US Standard

Construction

❖ BIAS

Machinery

Agriculture: Chargeuse-pelleteuse • Chargeuse télescopique

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
17.5L - 24	STANDARD	94061877	151 A8	12	DW 15L	DW 14L	17.7	50.8	22.7	151	TL	E11-106R-005232

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..