

TR 144 - Spécifications techniques



Description

TR 144 est adapté pour être utilisé sur les micro tracteurs dans les opérations de travail de la terre. TR 144 garantit des performances exceptionnelles dans toutes les conditions opérationnelles qui demandent une excellente traction associée à de charges élevés. Le pneu est aussi disponible en version « special », tout à fait appropriée aux opérations de service pénible.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Micro tracteur

Version	STANDARD
Type	TL
Tyre Size	9.5 - 16
LI/SS	92 A8

Dimensions US Standard

Usa code	94053551
Ply Rating	6
Section Width (inch)	9.6
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	15.3
Rolling Circumference (inch)	100.7
Rim Rec	W 8 L
Rim Alt	8 LB
ECE	E4-106R-002643
TRA Code	R1

Load capacity (lbs)

mph / psi	30
25	1390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 09:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..