

TR 173 - Spécifications techniques



Description

TR 173 est un pneu pour tracteurs adapté pour les terrains humides et les rizières. Le dessin particulier de la bande de roulement offre de grandes qualités d'auto-nettoyage et minimise le compactage du sol grâce à la large zone de contact.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	9.5 - 22
LI/SS	104 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	241
Overall Diameter (mm)	997
Static Loaded Radius (mm)	472
Rolling Circumference (mm)	3045
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-006485
TRA Code	R1W

Load capacity (Kg)

km/h / bar	2.20
30	900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..