

TR 273 - Spécifications techniques



Description

TR 273 est un pneu pour tracteurs adapté per les applications de travail de la terre. Ce pneu a été spécialement conçu pour offrir un maximum de performances sur les terrains humides et mouillés. Dans ces conditions de sol, un pneu doit offrir une adhérence supérieure et des propriétés élevées d'auto-nettoyage. TR 273 satisfait parfaitement à ces requêtes.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tracteur

Version	STANDARD
Type	TT
Tyre Size	18.4 - 34
LI/SS	150 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	475
Overall Diameter (mm)	1701
Static Loaded Radius (mm)	775
Rolling Circumference (mm)	5253
Rim Rec	DW 16A
Rim Alt	W16L,W15L,DW15L
ECE	E11-106R-004517
TRA Code	R2

Load capacity (Kg)

km/h / bar	2.20
30	3350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..