

## TR 273 - Spécifications techniques



### Description

TR 273 est un pneu pour tracteurs adapté per les applications de travail de la terre. Ce pneu a été spécialement conçu pour offrir un maximum de performances sur les terrains humides et mouillés. Dans ces conditions de sol, un pneu doit offrir une adhérence supérieure et des propriétés élevées d'auto-nettoyage. TR 273 satisfait parfaitement à ces requêtes.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Tracteur

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 23.1 - 30 |
| LI/SS     | 154 A8    |

## Dimensions US Standard

|                              |                   |
|------------------------------|-------------------|
| Usa code                     | 94045693          |
| Ply Rating                   | 14                |
| Section Width (inch)         | 23.2              |
| Overall Diameter (inch)      | 68.8              |
| Static Loaded Radius (inch)  | 31.3              |
| Rolling Circumference (inch) | 210.9             |
| Rim Rec                      | DW 20 A ; DW 20 B |
| ECE                          | E11-106R-003645   |
| TRA Code                     | R2                |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 28   |
| 25        | 8270 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 20:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..