

TR 315 - Fiche de données



Description

TR 315 est adapté pour les pelouses et les jardins et les opérations de travail de la terre et les services municipaux de voirie. Ce pneu est idéal pour être utilisé avec des outils agricoles, trancheuses et machines pour la récolte dans les vergers. TR 315 bénéficie d'une zone de contact large qui lui confère une excellente adhérence des qualités excellentes de autonettoyage ainsi qu'une stabilité exceptionnelle dans n'importe quelles conditions.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Tracteur pour vergers •
Trancheuse

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
16 X 6.50 - 8	STANDARD	4	5.375 I - 55 ; I - 70 ; I - 90		155	408	182	1183	TL	E11-106R-003493
16 X 6.50 - 8	STANDARD	6	5.375 I - 55 ; I - 70 ; I - 90		155	408	182	1183	TL	E4-106R-002175
23 X 10.50 - 12	STANDARD	4	8½ JA	7 JA	255	600	272	1840	TL	E4-106R-002179
23 X 10.50 - 12	STANDARD	6	8½ JA	7 JA	255	600	272	1840	TL	E4-106R-002177
23 X 10.50 - 12	STANDARD	8	8½ JA	7 JA	255	600	272	1840	TL	E4-106R-002661
23 X 10.50 - 12	STANDARD	10	8½ JA	7 JA	255	600	272	1840	TL	E11-106R-005206
23 X 10.50 - 12	STANDARD	12	8½ JA	7 JA	255	600	272	1840	TL	E11-106R-007639
23 X 8.50 - 12	STANDARD	4	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90		205	575	258	1668	TL	E11-106R-004518
23 X 8.50 - 12	STANDARD	6	7 JA ; 7.00 I - 55 ; I - 70 ; I - 90		205	575	258	1668	TL	E4-106R-002178
26 X 12.00 - 12	SPECIAL	10	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	TL	E11-106R-004519
26 X 12.00 - 12	STANDARD	4	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	TL	E11-106R-003494
26 X 12.00 - 12	STANDARD	8	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	TL	E4-106R-002674
26 X 12.00 - 12	STANDARD	10	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	TL	E11-106R-004519
26 X 12.00 - 12	STANDARD	12	10½ JA	8½ JA ; 9½ JA	308	655	289	1905	TL	E4-106R-002328
31 X 15.50 - 15	STANDARD	8	13 LB		390	800	354	2320	TL	E4-106R-002208
31 X 15.50 - 15	STANDARD	10	13 LB		390	800	354	2320	TL	E4-106R-001553
31 X 15.50 - 15	STANDARD	12	13 LB		390	800	354	2320	TL	E4-106R-002333

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..