

TR 318 - Fiche de données



Description

TR 318 a été spécialement conçu pour les machines d'irrigation et les outils agricoles. Les pavés à double angle assurent une excellente traction et un confort de conduite extraordinaire. TR 318 bénéficie aussi de formidables qualités d'auto-nettoyage.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Outillage agricole • Pulvérisateur

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
23 X 9.00 - 12	STANDARD	94070428	93 A3	6	7.0		8.7	23	TL	E11-106R-004521
23 X 9.00 - 12	STANDARD	94052110	93 A3	6	7.0		8.7	23	TT	E11-106R-004521
26 X 10.00 - 12	STANDARD	94052127	107 A3	8	8.5		10.4	26.6	TT	E11-106R-004522

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 11:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..