

TR 387 - Spécifications techniques



Description

TR 387 est un pneu agro-industriel, adapté pour les remorques pour canne à sucre et les compacteurs. Ce pneu se distingue de par sa capacité de charge élevée ainsi qu'une plus longue vie du pneu. Il est disponible en différentes versions afin de répondre aux exigences spécifiques des utilisateurs en termes de résistance aux coupures et déchirures, opérations de service pénible et durabilité. La version «dual bead», à double bourrelet, est particulièrement adaptée pour les tracteurs industriels et les opérations de transport avec remorques.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Remorque

Industriel: Compacteur

Version	HD
Type	TL
Tyre Size	23.1 - 26
LI/SS	164 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	592
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4688
SRI (mm)	750
Rim Rec	DW 20 B
ECE	E11-106R-003647
TRA Code	R3

Load capacity (Kg)

km/h / bar	1.70
30	5000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 03:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..