

TR 390 - Spécifications techniques



Description

TR 390 est un pneu agro-industriel, adapté pour les remorques pour canne à sucre et les compacteurs. Le pneu TR 390 se distingue de par une capacité de charge élevée et une durabilité supérieure. La version « dual bead HD », à double bourrelet HD, est particulièrement adaptée pour les tracteurs industriels et les opérations de transport avec remorques, tandis que la version « dual bead HD special », spéciale à double bourrelet HD, est idéale pour les opérations de service pénible.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Remorque
Industriel: Compacteur

Version	STANDARD
Type	TL
Tyre Size	28L - 26
LI/SS	150 A8

Dimensions US Standard

Usa code	94005239
Ply Rating	12
Section Width (inch)	28.1
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E11-106R-004608
TRA Code	R3

Load capacity (lbs)

mph / psi	20
25	7400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 08:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..